

WGP-C33/S-6

CUMMINS Series

Features:

- Rotate speed governor: Electrical governor
- Excitation system: Self excited, SHUNT
- A.V.R model: AS480
- Emergency stop switch
- ATS (automatic transfer switch) receptacle
- 24V sealed for life maintenance free battery
- Lockable battery isolator switch
- Powder coated canopy (Only for Soundproofed sets)
- 50°C radiator
- Oil pump on the engine
- Steel base frame with fork holes
- Vibration isolators between the engine/alternator and base frame
- Dry type air filter
- Base fuel tank for daily running
- Drain points for fuel tank
- Operation Manual / Specifications



Dimensions and Weights

Model	L	W	H
WGP-C33-6	1850	650	1250
WGP-C33S-6	2250	1050	1380

Output Ratings

Genset Model	Prime Power	Standby Power
WGP-C33-6	30kVA/24kW	33kVA/26kW
WGP-C33S-6	30kVA/24kW	33kVA/26kW

Ratings at 0.8 power factor

Notes:

*Prime Power

Continuous duty operation, under variable load 24/24h-10% over load

**Standby Power

Standby duty, operation under variable load, without over load;

Standard Reference Conditions

Note: Standard reference conditions 25°C (77°F) Air Inlet Temp, 100m(328 ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998,

Ratings and Performance Data

Engine Model:	Cummins 4B3.9-G2
Alternator Brand:	Stamford
Alternator Model:	PI 144E
Control System:	AMF
Circuit Breaker Type:	3 Pole MCCB
Frequency & Phase:	60Hz & 3PH
Engine Speed: RPM	1800
Fuel Tank Capacity: L	
WGP-C33-6	10 hrs
WGP-C33/S-6	10 hrs
Fuel Consumption: l/hr (100% Load)	
- Prime Power	5.6
- Standby Power	6.2

Engine Model: 4B3.9-G2

Engine Technical Data

No. of Cylinders / Alignment:	4 / In Line
Cycle:	4 Stroke
Bore / Stroke: mm	102/120
Induction:	Naturally
Cooling Method:	Water
Governing Type:	Mechanical
Governing Class:	ISO 8528 G2
Compression Ratio:	16.5:1
Displacement: L	3.9
Moment of Inertia:kg.m ²	0.143
Engine Electrical System:	
- Voltage / Ground	24/Negative
- Battery Charger	40 Amp
Weight: kg - Dry	308
- Wet	324

Performance

Engine Speed: RPM	1800
Gross Engine Power: kWm	
- Prime	30
- Standby	33
HP	
- Prime	/
- Standby	/

Lubrication System

Oil Pressure @ Idle Speed kPa	207
@ Rated Speed kPa	345
Maximum Oil Temperature: °C	121
Total Oil Capacity: L	11
Oil Type:	API CH4/15W-40

Exhaust System

Silencer Type	Industrial
Silencer Quantity:	1
Silencer Noise Reduction Level:	15 - 20dBA
Maximum Allowable Back Pressure: mmhg	76
Exhaust Gas Flow: l/s	
- Prime	67.5
- Standby	71.1
Exhaust Gas Temperature: °C	
- Prime	380
- Standby	410

Cooling System

Cooling System Capacity: L	7.2
Maximum coolant Friction Head	28
External to Engine: kPa	
Maximum Static Head of Coolant Above Engine Crank Centerline m :	14
Standard Thermostat (Modulating) Range: °C	82-95
Minimum Pressure Cap: kPa	69
Maximum Top Tank Temperature for Standby / prime Power: °C	104/100

Designed to operate in ambient conditions up to 50°C (122°F)
Contact a representative for power ratings at specific site conditions.

Fuel System

Injection System Type: BYC A Stanadyne				
Recommended Fuel Type:				
Diesel Fuel No.2-D(ASTMD975)				
Fuel Consumption: l/hr				
Prime Load	110%	100%	75%	50%
WGP-C33-6	6.2	5.6	4.5	3.3
WGP-C33/S-6	6.2	5.6	4.5	3.3

(Based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869,Class A2)

Air Systems

Air Filter Type:	Dry type replaceable Element
Intake Air Flow: l/s	
- Prime	32.8
- Standby	32.9
Max. Air Intake Restriction: mmH2O	
-With Dirty Filter Element	508
-With Normal Duty and Clean Filter	254
-With Heavy Duty and Clean Filter	305

Alternator Model: PI 144E

Alternator Physical Data

Manufactured by:	Stamford
Model:	PI 144E
No. of Bearings:	Single
Insulation Class:	H
Winding Pitch Code:	2/3
Wires:	12
Ingress Protection Rating:	IP23
Excitation System:	Self excited,shunt
AVR Model:	AS480

Alternator Operating Data

Overspeed: rpm	2250rpm
Voltage Regulation: (Steady state)	±1.0%
Wave Form NEMA = TIF:	<50
Wave Form IEC = THF:	<2%
Air Flow: m3/s	0.1
Altitude: m	≤1000

Alternator Performance Data:	WGP-C33-6	WGP-C33/S-6
Time constants/460V:Ms		
T'd	19	19
T''d	5	5
T'do	450	450
Ta	7	7
Short Circuit Capacity** %	1/Xd	1/Xd
Reactances: Per Unit		
Xd	1.61	1.61
X'd	0.15	0.15
X''d	0.11	0.11

Voltage Technical Data WGP-C33-6

Voltage	Prime kVA	Standby kVA
110/220	30	33
220/440	30	33
230/460	30	33
240/480	30	33

Voltage Technical Data WGP-C33/S-6

Voltage	Prime kVA	Standby kVA
110/220	30	33
220/440	30	33
230/460	30	33
240/480	30	33

Genset Controller DSE4620



Features:

- Large back-lit icon LCD display.
- 3-phase generator sensing.
- 3-phase generator and mains (utility) sensing.
- 600 V ph-ph nominal system compatibility.
- Generator & load power monitoring (kW, kV A, kV Ar, pf).
- Generator overload protection (kW).
- Configurable inputs & outputs.
- Fuel & crank outputs.
- Magnetic pick-up speed sensing.
- Battery voltage monitoring.
- Configurable event log (50).
- DSE Configuration Suite PC Software.
- Engine speed protection, engine hours counter, engine pre-heat, engine run-time scheduler, engine idle control for start/stop.

Genset Controller DSE7420




Features:

- Microprocessor control, with high stability and credibility .
- Mains supply and generator operation monitoring.
- Indicating operation status and fault conditions.
- Multiple protections; multiple parameters display such as pressure, temperature.
- Manual and automatic work mode selectable.
- Real time clock for time and date display, overall runtime display, 99 log entries
- Overall power output display.
- Integral speed/frequency detecting, telling status of start, rated operation, overspeed.
- Communication with PC via RS485 or RS232 interface, using MODBUS protocol.
- Engine ECU is available.
- Common USB cable is usable for parameter configuration.
- Multi-language is available

Optional

Engine	Alternator	Generator Set
<ul style="list-style-type: none"> • Water Jacket Preheater • Fuel-water separator • Oil pump • Oil preheater • Battery preheater 	<ul style="list-style-type: none"> • PMG excitation • Alternator heater • Winding Temperature Measuring • Anti-damp and anti-corrosion treatment • Anti-condensation heater 	<ul style="list-style-type: none"> •Tools with the machine •Coolant (-30°C)
Canopy	Fuel System	Control System
<ul style="list-style-type: none"> • Hired type • Trailer 	<ul style="list-style-type: none"> • Low fuel level alarm • Automatic fuel feeding system • Fuel T-valves • Dual Wall Integral Fuel Tanks • Dual Wall Sub-base Fuel Tanks • Automatic Fuel Fill Options • Fuel level shut down sensor 	<ul style="list-style-type: none"> • AMF function • ATS control cabinet • Double HZ & Volt • ABB & MCCB
Air Inlet system	Lube system	Starting /Charging system
<ul style="list-style-type: none"> • Air pre-heater 	<ul style="list-style-type: none"> • Manual sump pump • Lubricant oil pre-heater 	<ul style="list-style-type: none"> • Jacket water heater • Maintain free battery



WALT GLOBAL POWER EQUIPMENT CO.,LTD

E-mail: sales@waltpower.com

WALT reserves the right to make changes in model, technical specification, color, configuration and accessories without prior notice.

Please contact the salesman before ordering.

2018 by WALT, All right reserved