

WGP-C120/S-6

CUMMINS Series

Features:

- Rotate speed governor: Electrical governor
- Excitation system: Self excited
- A.V.R model: SX440
- Emergency stop switch
- ATS (automatic transfer switch) receptacle
- 24V sealed for life maintenance free battery
- Lockable battery isolator switch
- Powder coated canopy (Only for Soundproofed sets)
- 50°C radiator
- Oil pump on the engine
- Steel base frame with fork holes
- Vibration isolators between the engine/alternator and base frame
- Dry type air filter
- Base fuel tank for daily running
- Drain points for fuel tank
- Operation Manual / Specifications



Dimensions and Weights

Model	L	W	H
WGP-C120-6	2100	850	1480
WGP-C120/S-6	2900	1100	1650

Output Ratings

Genset Model	Prime Power	Standby Power
WGP-C120-6	110kVA/88kW	120kVA/96kW
WGP-C120/S-6	110kVA/88kW	120kVA/96kW

Ratings at 0.8 power factor

Notes:

*Prime Power

Continuous duty operation, under variable load 24/24h-10% over load

**Standby Power

Standby duty, operation under variable load, without over load;

Standard Reference Conditions

Note: Standard reference conditions 25°C (77°F) Air Inlet Temp, 100m(328 ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998,

Ratings and Performance Data

Cummins Engine Model:	6BT5.9-G2
Alternator Brand:	Stamford
Alternator Model:	UCI 274C
Control System:	AMF
Circuit Breaker Type:	3 Pole MCCB
Frequency & Phase:	60Hz & 3PH
Engine Speed: RPM	1800
Fuel Tank Capacity: L	
WGP-C120-6	10 hrs
WGP-C120S-6	10 hrs
Fuel Consumption: l/hr (100% Load)	
- Prime Power	20.2
-Standby Power	22.2

Engine Model: 6BT5.9-G2

Engine Technical Data

No. of Cylinders / Alignment:	6 / In Line
Cycle:	4 Stroke
Bore / Stroke: mm	102/120
Induction:	Turbocharged
Cooling Method:	Water
Governing Type:	Electrical
Governing Class:	/
Compression Ratio:	16.2:1
Displacement: L	5.9
Moment of Inertia:kg.m ²	0.25
Engine Electrical System:	
- Voltage / Ground	24/Negative
- Battery Charger	40 Amp
Weight: kg - Dry	411
- Wet	/

Performance

Engine Speed: RPM	1800
Gross Engine Power: kWm	
- Prime	100
- Standby	110
HP	
- Prime	/
- Standby	/

Lubrication System

Oil Pressure @ Idle Speed kPa	207
@ Rated Speed kPa	345
Maximum Oil Temperature: °C	121
Total Oil Capacity: L	16.4
Oil Type:	API CH4/15W-40

Exhaust System

Silencer Type	Industrial
Silencer Quantity:	1
Silencer Noise Reduction Level:	15 - 20dBA
Maximum Allowable Back Pressure: mmhg	76
Exhaust Gas Flow: l/s	
- Prime	250
- Standby	280
Exhaust Gas Temperature: °C	
- Prime	526
- Standby	565

Cooling System

Cooling System Capacity: L	25.1
Maximum coolant Friction Head	28
External to Engine: kPa	
Maximum Static Head of Coolant Above Engine Crank Centerline m :	14
Standard Thermostat (Modulating) Range: °C	82-95
Minimum Pressure Cap: kPa	69
Maximum Top Tank Temperature for Standby / prime Power: °C	104/100

Designed to operate in ambient conditions up to 50°C (122°F)
Contact a representative for power ratings at specific site conditions.

Fuel System

Injection System Type: BYC A Stanadyne				
Recommended Fuel Type:				
Diesel Fuel No.2-D(ASTM D975)				
Fuel Consumption: l/hr				
Prime	110%	100%	75%	50%
WGP-C120	22.2	20.2	16.2	12.1
WGP-C120/S-6	22.2	20.2	16.2	12.1

(Based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)

Air Systems

Air Filter Type:	Dry type
	replaceable Element
Intake Air Flow: l/s	
- Prime	100
- Standby	108
Max. Air Intake Restriction: mmH2O	
-With Dirty Filter Element	635
-With Normal Duty and Clean Filter Element	254
-With Heavy Duty and Clean Filter Element	381

Alternator Model: UCI 274C

Alternator Physical Data

Manufactured by:	Stamford
Model:	UCI 274C
No. of Bearings:	Single
Insulation Class:	H
Winding Pitch Code:	2/3
Wires:	12
Ingress Protection Rating:	IP23
Excitation System:	Self excited,shunt
AVR Model:	SX440

Alternator Operating Data

Overspeed: rpm	2250rpm
Voltage Regulation: (Steady state)	±1.0%
Wave Form NEMA = TIF:	<50
Wave Form IEC = THF:	<2%
Air Flow: m3/s	0.514
Altitude: m	≤ 1000

Alternator	WGP-C120-6	WGP-C120S-6
Performance Data:		
Time constants/400V:Ms		
T'd	28	28
T''d	1	1
T'do	800	800
Ta	7	7
Short Circuit Capacity** %	1/Xd	1/Xd
Reactances: Per Unit		
Xd	2.21	2.21
X'd	0.18	0.18
X''d	0.13	0.13

Voltage Technical Data WGP-C120-6

Voltage	Prime kVA	Standby kVA
110/220	110	120
220/440	110	120
230/460	110	120
240/480	110	120

Voltage Technical Data WGP-C120S-6

Voltage	Prime kVA	Standby kVA
110/220	110	120
220/440	110	120
230/460	110	120
240/480	110	120

Genset Controller DSE4620



Features:

- Large back-lit icon LCD display.
- 3-phase generator sensing.
- 3-phase generator and mains (utility) sensing.
- 600 V ph-ph nominal system compatibility.
- Generator & load power monitoring (kW, kV A, kV Ar, pf).
- Generator overload protection (kW).
- Configurable inputs & outputs.
- Fuel & crank outputs.
- Magnetic pick-up speed sensing.
- Battery voltage monitoring.
- Configurable event log (50).
- DSE Configuration Suite PC Software.
- Engine speed protection, engine hours counter, engine pre-heat, engine run-time scheduler, engine idle control for start/stop.

Genset Controller DSE7420




Features:

- Microprocessor control, with high stability and credibility .
- Mains supply and generator operation monitoring.
- Indicating operation status and fault conditions.
- Multiple protections; multiple parameters display such as pressure, temperature.
- Manual and automatic work mode selectable.
- Real time clock for time and date display, overall runtime display, 99 log entries
- Overall power output display.
- Integral speed/frequency detecting, telling status of start, rated operation, overspeed.
- Communication with PC via RS485 or RS232 interface, using MODBUS protocol.
- Engine ECU is available.
- Common USB cable is usable for parameter configuration.
- Multi-language is available

Optional

Engine	Alternator	Generator Set
<ul style="list-style-type: none"> • Water Jacket Preheater • Fuel-water separator • Oil pump • Oil preheater • Battery preheater 	<ul style="list-style-type: none"> • PMG excitation • Alternator heater • Winding Temperature Measuring • Anti-damp and anti-corrosion treatment • Anti-condensation heater 	<ul style="list-style-type: none"> •Tools with the machine •Coolant (-30°C)
Canopy	Fuel System	Control System
<ul style="list-style-type: none"> • Hired type • Trailer 	<ul style="list-style-type: none"> • Low fuel level alarm • Automatic fuel feeding system • Fuel T-valves • Dual Wall Integral Fuel Tanks • Dual Wall Sub-base Fuel Tanks • Automatic Fuel Fill Options • Fuel level shut down sensor 	<ul style="list-style-type: none"> • AMF function • ATS control cabinet • Double HZ & Volt • ABB & MCCB
Air Inlet system	Lube system	Starting /Charging system
<ul style="list-style-type: none"> • Air pre-heater 	<ul style="list-style-type: none"> • Manual sump pump • Lubricant oil pre-heater 	<ul style="list-style-type: none"> • Jacket water heater • Maintain free battery



WALT GLOBAL POWER EQUIPMENT CO.,LTD

E-mail: sales@waltpower.com
 Walt reserves the right to make changes in model, technical specification, color, configuration and accessories without prior notice.
 Please contact the salesman before ordering.
 2018 by WALT, All right reserved